



LF30 Controller

Jagoteq Controller for Side Emitting Fiber Optic

Superior Technology

- Combining multiple lasers into one light source with an infinite amount of light color options
- Emits light at 360 degrees
- Direct replacement of LED technology with brighter and more saturated color light output

Efficient and Cost Effective

- No change in work methods required for lighting professionals
- Simple installation process that reduces labor hours and material costs
- Requires no additional hardware

Environmentally Friendly

- Can be reused indefinitely with care
- Aligns with studios goals for ESG initiatives
- Fiber optic cable can be recycled

Controller Features:

Data Control: 5 pin DMX control
Ethernet: Allows for control via Artnet/sACN
Bluetooth
Power input
120V-12V DC Barrel Connector
Firmware updates: USB-C port
Fiber Connection: SMA-905
Fiber Optic cable Outputs: 1
Power consumption: 2 A
UI: 2x3.1" color screens
Managed by 4-way touch pad
Screens are dimmable
Cooling: Heat sink/Smart Fan Control
Ambient operating temperature: 34F-90F
Noise Level: 45dB at full operating power allow
for use on film/TV sets
Quiet and Super Quiet Modes for limited time

Weight: 1.5lbs
Dimensions: 4"W x 3"H x 6"D
Material: High Impact Plastic
Vinyl Wrap
Rigging points: 1/4" 20
female inserts
"D" rings
Mounting Flange on 2 sides

Fiber Compatibility: 1mm and 6mm

Handling: Must be
handled with care

Safety: Auto cut off when fiber optic cable is compromised
Safety Certifications: ETL, CA, 3R, CE in UKCA (in process)
ROHS compliant

Sales/Rental: Craig Brink 310-740-1255 Craig@jagoteq.com
MENA Region Distributor: Muhannad Malki 818-620-6540 malki@jagoteq.com

